PRE-PRESS

GALVANIC | ENGRAVING | CYLINDER CORRECTION | MEASURING DEVICES

MILLING OFF AND TURNING OFF COPPER

		Order No.	Product	Application / Property		
		CUTTING OIL	S			
			which are treated with a Polishmaster; off; non-toxic and non-polluting; life-1	oils are effective even as very thin film on the surface; no smoke time of the cutting tools is increased		
		A03-0531	Cutting Oil T2002	Acecor 15703 and T2002 are completely water-soluble and therefore easy to remove		
		M14-00104	Cutting Oil D1	D1 is not completely mixible with water; it differs in content of grease and the removal is more large scale; such greasy oil works as protective film while storing the cylinders		
		GENERAL PRODUCTS FOR MILLING OFF AND TURNING OFF COPPER				
•	C	A03-0534	Hydrofluid	Concentrate for hydrostatics		
	Ø.	A01-0100 ff.	Cutting Tools for Polishmaster	Rough-, fine- and side-cutting tool		
	Ø	A01-0089 A01-0161/N	Cutting Tool for CFM-Machine Polycrystalline tool for Superperfast	Face cutting tool		
		A01-0128	Side Cutting Tool resp. Insert for side cutters	Side cutting tool (for CFM-Machine resp. Superperfast)		

FILTER MATERIAL FOR GALVANIC BATHES

	Order No.	Product	Application / Property
ЬT	B03-0508 ff.	Depth Filter Cartridges PUR	Polypropylen fi lters (depth fi lter) for cleaning of electrolytic solutions; strong dirt absorption over the whole filter depth; long life-time; wide chemical compatibility; available in various lengths (10", 20") and µm-sizes (1, 3, 5, 10, 20 µm)
	B03-0534 ff.	Wounded filter Cartridges 10" and 20"	Wounded PP filter cartridges in various μm-sizes (e.g. 1 μm, 10 μm, etc.)
	B03-0455 ff.	Activated Carbon Filter Cartridges 10" and 20"	For removal of organic compounds in electrolytical solutions
	B03-0302 ff.	Filter Disks	For Cleaning of electrolytical solutions; available with customized sizes and thicknesses; made of paper or card-board
	B03-0450 ff.	Activated Carbon Filter Disks	For removal of organic compounds in electrolytical solutions; available with customized sizes and thicknesses
	B03-0990 ff.	Filter Fleece HM50, T40 or T70 V60 and HD 130	Filter fleece for band filter system, Length: 100 m or 200 m; Width: 480 mm or 750 mm